

**DESCRIPTION**

Comp 50 Plus is a 25W-70 shear stable competition motor oil. It is formulated to give optimum protection to engines operating under severe conditions on water, road or track. Also suited to older vehicles and worn engines. Helps significantly reduce oil consumption and smoke from worn engines. Incorporates an additive pack specially designed for the motor enthusiast running very high performance engines with high bearing clearance. The product is the oil of choice for Gulf Westerns TOP FUEL Nitro drag team and various TOP ALCOHOL race teams.

**SUMMARY OF BENEFITS**

- Formulation has a boosted level of Zinc (ZDDP) anti-wear additive to protect against cam lobe and follower scuffing that can occur in heavily loaded valve gear of modified engines
- Suitable for big V twin motor cycle engines, such as Harley Davidson
- Can also be used for lightly loaded diesel engines and turbo-charged race engines
- Suitable for methanol fuelled engines

**SPECIFICATIONS**

- SAE VISCOSITY 25W-70
- API SN/CF

**SUITABLE FOR**



COMP 50 PLUS	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.888
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	280
@ 100°C	ASTM D445	cSt	26
VISCOSITY INDEX	ASTM D2270	-	120
POUR POINT	ASTM D97	°C	-24
FLASH POINT (COC)	ASTM D92	°C	>205

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

205LT - #30024, 20LT - #32024 AND 5LT - #30524